

Description

SPC12-0.5 is an automatic battery charger, best suited for home medical equipment, wheelchairs, scooters, mobility and other applications. The charger works best with batteries rated between 1 Amp and 3.5 Amp. SPC12-0.5 comes with 1 year warranty and is overseas ready.



General Characteristics

Over Load Protection	<0.8A
Short Circuit Protection	Enable
Reversed Polarity Protection	Enable
Operating Temperature	0°C(32°F) to 40°C(104°F)
Storage Temperature	-30°C(-22°F) to 85°C(185°F)
Operating Relative Humidity	8% to 90%
Storage Relative Humidity	5% to 95%

Applications

- Sealed Lead Acid Battery



Input



AC Input Voltage Range	90Vac to 264Vac
AC Input Voltage Rating	100Vac to 240Vac
AC Input Frequency	50/60Hz
AC Input Current	0.14A@115Vac / 0.1A@230Vac
AC Input Power	8.8W (max.)
AC Input Static State Current	35mA (max.)

Output


Output Voltage Range	10Vdc to 15Vdc
Output Current	0.5A@12Vdc (±10%)
Output Power	7.5W (max.)
Bulk Charge Current Rating	0.5A
Bulk Charge Voltage Rating	14.7Vdc (±0.3Vdc)
Float Charge Voltage Rating	13.5V - 13.95Vdc
Light Switching Current	100mA (±25mA)

Dimensions (mm/inch)

Length	Width	Height	Weight
82 / 3.23	56 / 2.19	47 / 1.85	0.20kg / 0.45lb



Charger Characteristics



Indicator Status

- Green LED on - Empty Load or Float Charge
- Red LED on - Bulk Charge

Contact Information

SigmasTek
7651 W 100th Place
Bridgeview, IL 60455, USA

T: (888) 988-8290
www.sigmastek.com
order@sigmastek.com